

AVISTA pace GER SAE 5W-30

Optimally adapted car engine oil (petrol, diesel). Particularly developed for the requirements of German types of vehicle.

APPLICATION

- car, petrol, diesel
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

CHARACTERISTICS

- low evaporation loss and low cam wear
- good oxidation stability
- piston cleanliness
- outstanding cleaning and dispersion properties
- prevents oil inspissation

APPROVALS

API SL
MB-Freigabe 229.3

SPECIFICATIONS

ACEA A3/B4
A3/B3
Renault RN 0700 / 0710
VW 502 00 / 505 00

RECOMMENDATIONS

MB 226.5

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		5W-30
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	11.1 – < 12.5
Viscosity Index	ASTM D2270		min. 161
Total Base Number	ASTM D2896	mg KOH/g	10.0 – 12.4
Dyn. Viscosity @ -30 °C	ASTM D5293	mPa*s	max. 6,600
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-number 6)