

AVISTA pace GER SAE 5W-40

Optimally adapted car engine oil (petrol, diesel). Particularly developed for the requirements of German types of vehicle.

APPLICATION

- Car, petrol, diesel

CHARACTERISTICS

- low evaporation loss and low cam wear
- good oxidation stability
- piston cleanliness
- outstanding cleaning and dispersion properties
- prevents oil inspissation

APPROVALS

API	SN
MB-Freigabe	229.3
Porsche	A40
Renault	RN 0700 / 0710
VW	502 00 / 505 00

SPECIFICATIONS

ACEA	A3/B4, A3/B3
-------------	--------------

RECOMMENDATIONS

Fiat	9.55535-M2
General Motors	GM-LL-A-025 GM-LL-B-025
MB	226.5

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		5W-40
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.835 – 0.875
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	13.4 – 14.8
Viscosity Index	ASTM D2270		min. 166
Total Base Number	ASTM D2896	mg KOH/g	10.0 – 12.4
Dyn. Viscosity @ -30°C	ASTM D5293	mPa*s	max. 6,600
Flash point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Nummer 6)