

## AVISTA pace GER FS SAE 10W-40

**Optimised car engine oil (petrol, diesel). Especially designed for older Daimler models. Proven and tested in practice in engines with fluid specification API CF.**

### APPLICATION

- passenger car (petrol, diesel)
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

### CHARACTERISTICS

- low evaporation loss
- good oxidation stability
- piston cleanliness
- outstanding cleaning and dispersion properties
- prevents oil thickening

### APPROVALS

API SN

### SPECIFICATIONS

ACEA A3/B4  
API CF  
MB 229.1  
Renault RN 0700

### RECOMMENDATIONS

VW VW 501 01 / 505 00

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		10W-40
Density 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.840 – 0.880
Kin. Viscosity @ 100 °C	ASTM D7279	mm <sup>2</sup> /s	13.3 – 14.7
Viscosity Index	ASTM D2270		min. 150
Total Base Number	ASTM D2896	mg KOH/g	10.0 – 12.4
Dyn. Viscosity @ -25 °C	ASTM D5293	mPa*s	max. 7,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -39

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 8)