

AVISTA pace GER FS SAE 15W-40

Best tuned passenger car engine oil (petrol, diesel). Developed especially for older Daimler models.

APPLICATION

- car, engine oil (petrol, diesel)
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

CHARACTERISTICS

- low evaporation loss
- great oxidation stability
- piston cleanliness
- outstanding cleaning and dispersing properties
- prevents oil thickening

APPROVALS

API SL

SPECIFICATIONS

MB 229.1

RECOMMENDATIONS

MAN M3275-1
MB 228.3 (V2012.1)
MTU TYPE 2
Volvo VDS

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		15W-40
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.845 – 0.885
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	13.7 – 14.7
Viscosity Index	ASTM D2270		min. 140
Total Base Number	ASTM D2896	mg KOH/g	8.1 – 9.7
Dyn. Viscosity @ -20 °C	ASTM D5293	mPa*s	max. 7,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 6)