

## AVISTA pace SN SAE 10W-30

Universal passenger car engine oil for a wide range of vehicles, to meet all requirements of API specifications SA to SN.

Can also be used for passenger cars of the brands Aston Martin, BMW, Buick, Cadillac, Chery, Chevrolet, Chrysler, Dacia, Daihatsu, Dodge, Fiat, Ford, Genesis, GMC, Honda, Hyundai, Infiniti, JAC, Jeep, Kia, Lada, Land Rover, Lexus, Lotus, Mazda, MG, Mitsubishi, Nissan, Pontiac, Porsche, Renault, Saab, Subaru, Suzuki, Toyota, Volvo in compliance with the manufacturer's instructions.

### APPLICATION

- Car, petrol

### CHARACTERISTICS

- small deposits and wear
- better properties than API SM referring resistance to aging
- stability of viscosity
- fuel saving
- low exhaust gas emission
- engine cleanliness
- piston cleanliness
- flexible maintenance intervals

### SPECIFICATIONS

API SN

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 10W-30
Density 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.841 – 0.861
Kin. Viscosity @ 100 °C	DIN 51562-1	mm <sup>2</sup> /s	9.9 – 11.5
Viscosity Index	DIN ISO 2909		min. 145
Total Base Number	DIN ISO 3771	mg KOH/g	7.5 – 9.0
Dyn. Viscosity @ -25°C	DIN 51377	mPa*s	max. 7.000
Flash point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 4)