

## AVISTA pace SN SAE 10W-60

Universal passenger car engine oil for a wide range of vehicles, to meet all requirements of API specifications SA to SN.

Can also be used for passenger cars of the brands Alfa Romeo, Aston Martin, Lancia, Lotus, Maserati in compliance with the manufacturer's instructions.

### APPLICATION

- Car, petrol

### CHARACTERISTICS

- Small deposits and wear
- better properties than API SM
- regarding aging resistance
- stability of viscosity
- fuel-saving
- low exhaust gas emission
- engine cleanliness
- piston cleanliness
- flexible maintenance intervals

### RECOMMENDATIONS

API SN

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 10W-60
Density 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm <sup>2</sup> /s	23.3 – 24.7
Viscosity Index	ASTM D2270		min. 170
Total Base Number	ASTM D2896	mg KOH/g	7.0 – 9.0
Dyn. Viscosity @ -25°C	ASTM D5293	mPa*s	max. 7.000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 5)