

AVISTA pace SN SAE 5W-30

Universal passenger car engine oil for a wide range of vehicles, to meet all requirements of API specification SN.

APPLICATION

- Car, petrol

CHARACTERISTICS

- Small deposits and wear
- better properties than API SM referring resistance to aging
- stability of viscosity
- fuel saving
- low exhaust gas emission
- engine cleanliness
- piston cleanliness
- flexible maintenance intervals

SPECIFICATIONS

API SN

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 5W-30
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	10.1 – 11.5
Viscosity Index	ASTM D2270		min. 157
Total Base Number	ASTM D2896	mg KOH/g	7.2 – 9.2
Dyn. Viscosity @ -30°C	ASTM D5293	mPa*s	max. 6.600
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 5)