

AVISTA pace CLASSIC SA SAE 30

Monograde engine oil (petrol) for various applications, especially when good lubrication performance is required at low and high temperatures.

APPLICATION

- Cars (engine), commercial vehicles, petrol

CHARACTERISTICS

- Monograde engine oil
- oxidation-stable
- not foaming
- first-class viscosity-temperature behaviour
- low setting point
- lubrication performance at low and high temperatures depending on viscosity

APPROVALS

SPECIFICATIONS

RECOMMENDATIONS

API

SA

TYPICAL CHARACTERISTICS

(The given data are typical data.)

| Parameter | Method | Unit | |
|-------------------------|------------------|--------------------|---------------|
| SAE Class | SAE J 300 | | 30 |
| Density @ 15 °C | DIN EN ISO 12185 | g/cm ³ | 0.865 – 0.895 |
| Kin. Viscosity @ 100 °C | ASTM D7279 | mm ² /s | 10.8 – 12.2 |
| Neutralisation Number | DIN ISO 6618 | mg KOH/g | max. 0.15 |
| Flash Point COC | DIN ISO 2592 | °C | min. 200 |
| Pour Point | ASTM D7346 | °C | max. -24 |

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 2)