

AVISTA pace CLASSIC SF/CD SAE 20W-50

Multigrade engine oil (petrol, diesel) for various applications, especially when good lubrication performance is required at low and high temperatures.

APPLICATION

- Cars (engine), commercial vehicles, petrol, diesel

CHARACTERISTICS

- Multigrade engine oil
- powerful
- oxidation-stable
- not foaming
- first-class viscosity-temperature behaviour
- low setting point
- lubrication performance at low and high temperatures depending on viscosity

APPROVALS

SPECIFICATIONS

RECOMMENDATIONS

API SF
CD

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		20W-50
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.860 – 0.900
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	17.5 – 18.9
Viscosity Index	ASTM D2270		min. 120
Total Base Number	ASTM D2896	mg KOH/g	3.8 – 5.2
Dyn. Viscosity @ -15°C	ASTM D5293	mPa*s	max. 9,500
Flash point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -27

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Nummer 4)