

## AVISTA pace CLASSIC SJ/CF-4 SAE 10W

High-alloyed HD monograde engine oil (petrol, diesel) for older models of the mixed vehicle fleet, especially when first-class lubrication performances are required at low temperatures.

### APPLICATION

- Cars (engine), commercial vehicles, petrol, diesel

### CHARACTERISTICS

- High-alloyed HD-monograde engine oil
- first-class wear protection properties of detergent/dispersant additives
- can be mixed with all HD-engine oils based on mineral oils
- lubrication performance at low and high temperatures depending on viscosity

### APPROVALS

### SPECIFICATIONS

### RECOMMENDATIONS

API SJ  
CF-4

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		10W
Density @ 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.840 – 0.800
Kin. Viscosity @ 100 °C	ASTM D7279	mm <sup>2</sup> /s	6.3 – 7.7
Viscosity Index	ASTM D2270		min. 117
Total Base Number	ASTM D2896	mg KOH/g	7.3 – 9.3
Dyn. Viscosity @ -25°C	ASTM D5293	mPa*s	max. 7.000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Nummer 4)