

AVISTA pace CLASSIC SJ/CF-4 SAE 40

High-alloyed HD monograde engine oil (petrol, diesel) for older models of the mixed vehicle fleet, especially when first-class lubrication performances are required at low and high temperatures.

APPLICATION

- Cars (engine), commercial vehicles, petrol, diesel

CHARACTERISTICS

- High-alloyed HD-monograde engine oil
- first-class wear protection properties of detergent/dispersant additives
- can be mixed with all HD-engine oils based on mineral oils
- lubrication performance at low and high temperatures depending on viscosity

APPROVALS

SPECIFICATIONS

RECOMMENDATIONS

API SJ
CF-4

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		40
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.865 – 0.895
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	13.8 – 15.2
Total Base Number	ASTM D2896	mg KOH/g	7,3 – 9,3
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -27

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Nummer 3)