

AVISTA pace EVO C2 SAE 0W-30

Fuel-saving car engine oil (petrol, diesel) of the AVISTA pace EVO line for vehicles with modern after-treatment of exhaust gas and longer maintenance intervals for meeting of all requirements of the ACEA specification C2 and the OEM approvals stated.

APPLICATION

- Car, light commercial vehicles, petrol, diesel, with modern after-treatment of exhaust gas
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

CHARACTERISTICS / APPLICATION BENEFITS

- mid SAPS
- aging resistance
- stability of viscosity
- fuel-saving
- low exhaust gas emissions
- low wear
- engine cleanliness
- longer maintenance interval

APPROVALS

SPECIFICATIONS

ACEA C2

RECOMMENDATIONS

API SN
 Ford WSS-M2C950-A
 Jaguar/Land Rover STJLR.03.5007

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 0W-30
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.825 – 0.855
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	9.3 – 10.7
Viscosity Index	DIN ISO 2909		min. 190
Total Base Number	DIN ISO 3771	mg KOH/g	7.3 – 9.3
Dyn. Viscosity @ -35 °C	DIN 51377	mPa*s	max. 6,200
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -39

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 7)