

AVISTA pace EVO EUR SAE 0W-20

Fuel saving, easy running car engine oil (petrol, diesel) of the AVISTA pace EVO line with outstanding properties referring engine cleanliness and resistance to aging. Particularly developed for the requirements of European types of vehicle.

APPLICATION

- car, engine oil (petrol, diesel)
- hybrid vehicles
- possibly engines with additional gas tank (please observe the respective OEM manufacturer's specifications)

CHARACTERISTICS

- fuel saving
- reduced-SAPs
- small deposits and wear
- resistance to aging
- stability of viscosity
- low exhaust gas emission
- engine cleanliness
- piston cleanliness
- longer maintenance interval

SPECIFICATIONS

ACEA	C5
API	SN

RECOMMENDATIONS

MB	229.71
Jaguar/Land Rover	STJLR.51.5122

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		0W-20
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.825 – 0.855
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	7.0 – 8.5
Viscosity Index	DIN ISO 2909		min. 180
Total Base Number	DIN ISO 3771	mg KOH/g	7.0 – 8.4
Dyn. Viscosity @ -35 °C	DIN 51377	mPa*s	max. 6,200
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 6)