

## AVISTA pace EVO GER SAE 0W-40

Powerful, easy running car engine oil (petrol, diesel) of the AVISTA pace EVO line with outstanding cleaning and dispersion properties. Particularly developed for the requirements of German types of vehicle.

### APPLICATION

- car, petrol, diesel
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

### CHARACTERISTICS

- low evaporation loss and low cam wear
- good oxidation stability
- piston cleanliness
- outstanding cleaning and dispersion properties
- prevents oil inspissation

### APPROVALS

### SPECIFICATIONS

API	SN
ACEA	A3/B4
MB	229.5

### RECOMMENDATIONS

BMW	LL 01 (N52)
Fiat	9.55535-M2
Ford	WSS-M2C937-A
MB	229.3
	226.5
Porsche	A40
Renault	RN 0700 / 0710
VW	502 00 / 505 00

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		0W-40
Density @ 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.825 – 0.865
Kin. Viscosity @ 100 °C	ASTM D7279	mm <sup>2</sup> /s	12.8 – 14.2
Viscosity Index	ASTM D2270		min. 172
Total Base Number	ASTM D2896	mg KOH/g	10.0 – 12.4
Dyn. Viscosity @ -35 °C	ASTM D5293	mPa*s	max. 6,200
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. - 42

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 7)