

AVISTA pace EVO PRIME GER SAE 5W-30

Powerful and fuel saving, high-performance easy running car engine oil (petrol, diesel) of the AVISTA pace EVO line with excellent properties referring engine cleanliness and resistance to aging. Particularly developed for the requirements of German types of vehicle.

APPLICATION

- Car, petrol, diesel, not backward compatible (referred to MB release 229.6)
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

CHARACTERISTICS

- extremely fuel-saving
- small deposits and wear
- resistance to aging
- stability of viscosity
- low exhaust gas emission
- engine cleanliness
- piston cleanliness
- longer maintenance interval

APPROVALS

SPECIFICATIONS

RECOMMENDATIONS

API	SL
ACEA	A5/B5, A1/B1
MB	229.6

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		5W-30
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.840 – 0.870
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	9.3 – 10.7
Viscosity Index	DIN ISO 2909		min. 155
Total Base Number	DIN ISO 3771	mg KOH/g	9.4 – 11.0
Dyn. Viscosity @ -30°C	DIN 51377	mPa*s	max. 6,600
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -39

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 4)