

AVISTA peer ATF 1000

Automatic transmission oil, where TASA is required with exceptionally good aging resistance, outstanding viscosity-temperature behaviour, effective wear protection, as well as best lubrication properties and extremely low setting point.

APPLICATION

- Automatic transmissions, where TASA is required
- The product is red coloured.

CHARACTERISTICS / APPLICATION BENEFITS

- good aging resistance
- outstanding viscosity-temperature behaviour
- effective wear protection
- best lubrication properties
- low setting point

APPROVALS

SPECIFICATIONS

RECOMMENDATIONS

Dexron

TASA

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 306		75W
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	6.8 – 8.2
Viscosity Index	ASTM D2270		min. 147
Brookfield @ -40°C	DIN 51398	mPa*s	max. 50,000
Flash point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -45

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 5)