

AVISTA peer ATF 2000

Automatic transmission oil, where Dexron II-D is required with exceptionally good Aging resistance, outstanding viscosity-temperature behaviour, effective wear protection, as well as best lubrication properties and extremely low setting point.

APPLICATION

- Automatic transmissions, where Dexron II-D is required
- The product is field-tested for application where GM Motors Type A Suffix A (TASA) is recommended.
- The product is red coloured.

CHARACTERISTICS / APPLICATION BENEFITS

- First-class, very shear-stable viscosity-temperature behaviour
- no problems at low/high temperatures
- thermally high loadability
- foam-free under heaviest loads
- neutral behaviour against sealing materials

APPROVALS

SPECIFICATIONS

RECOMMENDATIONS

Dexron II-D

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 306		75W
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	7.6 – 9.0
Brookfield @ -40°C	DIN 51398	mPa*s	max. 20,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -48

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 8)