

## AVISTA peer CLASSIC GL3 SAE 90

Car gearbox for older models for which good lubrication properties and good temperature-viscosity behaviour are required.

### APPLICATION

- Car gearbox (older models)

### CHARACTERISTICS

- good lubrication properties
- good temperature-viscosity behaviour

### APPROVALS

### SPECIFICATIONS

### RECOMMENDATIONS

API

GL3

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		90
Density 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.870 – 0.900
Kin. Viscosity @ 40 °C	DIN 51562 -1	mm <sup>2</sup> /s	135 – 165
Kin. Viscosity @ 100 °C	DIN 51562-1	mm <sup>2</sup> /s	15.0. – 17.0
Viscosity Index	DIN ISO 2909		min. 95
Neutralisation Number	DIN ISO 6618	mg KOH/g	0.30 – 0.70
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -24

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Nummer 1)