

AVISTA peer EVO ATF 2000

High-grade automatic transmission oil of the AVISTA peer EVO line meeting the Dexron II-D specification, as well as many OEM approvals. The product is field-tested for application where GM Motors Type A Suffix A (TASA) is recommended.

APPLICATION

- automatic transmissions
- the product is red coloured.

CHARACTERISTICS / APPLICATION BENEFITS

- first-class, very shear-stable viscosity-temperature behaviour
- no problems at low / high temperatures
- thermally high loadability
- foam-free under heaviest loads
- neutral behaviour against sealing materials

APPROVALS

DTFR	13C100 (MB 236.1)
MAN	MAN 339 Typ L-2 / V-1 / Z-1
ZF	ZF TE-ML 03D, 04D, 14A, 17C (ZF004775)

SPECIFICATIONS

GM	Dexron II-D
Ford	Mercon
Voith	55.6335.xx

RECOMMENDATIONS

Allison	C-4
Caterpillar	TO-2
Renk Doromat	Renk Doromat
ZF	ZF TE-ML 11B

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 306		75W
Density @15 °C	DIN EN ISO 12185	g/cm ³	0.835 – 0.875
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	7.5 – 8.9
Brookfield @ -40°C	DIN 51398	mPa*s	max. 50,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -48

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 10)