

AVISTA peer EVO ATF GER

Superior automatic transmission oil of the AVISTA peer EVO line especially developed for transmissions of German manufacturers.

APPLICATION

- Automatic transmissions, especially German manufacturers.

CHARACTERISTICS

- Excellent flowability at low temperatures
- clean, comfortable shifting processes

APPROVALS

SPECIFICATIONS

RECOMMENDATIONS

Mercedes-Benz-Blatt	236.1
	236.2
	236.3
	236.5
	236.6
	236.7
	236.9
	236.10 (NAG 1 / Shell 3403)
	236.11
	236.81

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 306		75W
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.825 – 0.865
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	6.2 – 7.6
Brookfield @ -40°C	ASTM D5293	mPa*s	max. 20,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -42

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Nummer 2)