

AVISTA peer EVO GL4 SAE 75W-90

Highly modern multipurpose gear oil of the AVISTA peer EVO line for the use throughout the year in extremely loaded control/differential/steering gears, where the requirements of API specification GL4 and further OEM regulations must be met.

APPLICATION

- control gear
- differential gear
- steering gear

CHARACTERISTICS / APPLICATION BENEFITS

- high load carrying ability
- very good wear protection
- very good viscosity-temperature behaviour
- low setting point
- it prevents the formation of foam
- shear stability
- applicable throughout the year

APPROVALS

SPECIFICATIONS

RECOMMENDATIONS

API

GL4

TYPICAL CHARACTERISTICS

(The given data are typical data.)

| Parameter | Method | Unit | |
|-------------------------|------------------|--------------------|---------------|
| SAE Class | SAE J 306 | | 75W-90 |
| Density @ 15 °C | DIN EN ISO 12185 | g/cm ³ | 0.855 – 0.895 |
| Kin. Viscosity @ 100 °C | ASTM D7279 | mm ² /s | 15.8 – 17.7 |
| Brookfield @ -40°C | DIN 51398 | mPa*s | max. 150,000 |
| Flash Point COC | DIN ISO 2592 | °C | min. 200 |
| Pour Point | ASTM D7346 | °C | max. -42 |

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 5)