

AVISTA peer EVO GL 4 80W-90

Multipurpose gear oil for the application in control/differential/steering gears, for meeting of all requirements of the API specification GL4.

APPLICATION

- control gear
- differential gear
- steering gear

CHARACTERISTICS / APPLICATION BENEFITS

- high load carrying ability
- wear protection
- oxidation stability
- low gel point

APPROVALS

ZF ZF TE-ML 16A, 17A, 19A
(ZF004779)

SPECIFICATIONS

RECOMMENDATIONS

API GL4
MAN MAN 341 Typ E-1
MAN 341 Typ Z-2

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 306		SAE 80W-90
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.870 – 0.910
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	14.3 – 15.7
Brookfield @ -26°C	DIN 51398	mPa*s	max. 150,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -27

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 6)