

AVISTA peer EVO GL5 LS SAE 90

Highly modern multipurpose gear oil of the AVISTA peer EVO line for the use throughout the year in axle/hypoid gears, with well-known OEM approvals.

APPLICATION

- Axle gear
- Hypoid gear, with differential lock

CHARACTERISTICS / APPLICATION BENEFITS

- very high load carrying ability
- very high wear protection due to extreme-pressure-additives
- very good foam/air separation behaviour
- very good viscosity-temperature behaviour
- applicable throughout the year

APPROVALS

ZF ZF TE-ML 05C, 16E, 21C
(ZF004776)

SPECIFICATIONS

ZF TE-ML 12C

RECOMMENDATIONS

API GL5
Liebherr Liebherr
(P: min. 1.900 ppm)

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 306		SAE 90
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.880 – 0.920
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	16.8 – 18.2
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -12

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 6)