

## AVISTA peer EVO PRIME ATF GER

Low-viscous automatic transmission oils of the AVISTA peer EVO PRIME-line, for the universal use for transmissions made by the manufacturer Daimler.

### APPLICATION

- Automatic transmissions, especially of German manufacturers

### CHARACTERISTICS / APPLICATION BENEFITS

- low viscous
- good friction coefficient
- high shifting comfort

### EMPFEHLUNGEN

**Mercedes-Benz-Blatt** 236.12, 236.14, 236.15, 236.16, 236.17, 236.41  
**ZF** 6-Speed (e. g. 6HP19, 6HP26, 6HP28, 6HP32)

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 306		75W
Density @ 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.825 – 0.865
Kin. Viscosity @ 100 °C	ASTM D7279	mm <sup>2</sup> /s	5.0 – 6.4
Brookfield @ -40°C	DIN 51398	mPa*s	max. 15,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -42

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 5)