

AVISTA pulse EVO 4 STROKE SAE 10W-60

Four-stroke engine oil of the AVISTA pulse EVO line for motorcycles with wet and oil-lubricated couplings for meeting all requirements of the JASO MA 2 specification.

APPLICATION

- four-stroke motorcycles with wet couplings

CHARACTERISTICS / APPLICATION BENEFITS

- complete adhesion of lubrication film
- superior friction ability

RECOMMENDATIONS

JASO MA 2
API SN

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE class	SAE J 300		SAE 10W-60
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	22.0 – 23.4
Viscosity Index	ASTM D2270		min. 170
Total Base Number	ASTM D2896	mg KOH/g	5.6 – 7.0
Dynamic Viscosity @ -25 °C	ASTM D5293	mPa*s	max. 7,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -39

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 5)