

AVISTA pulse EVO PRIME 2 STROKE

Most advanced PIB-based (synthetic) high-performance two-stroke oil of the AVISTA pulse EVO PRIME line for air- and water-cooled engines, especially for two-stroke motorcycles for meeting of all requirements of the JASO FD / ISO-L-EGD.

APPLICATION

- air- and water-cooled two-stroke engines (petrol)
- especially for two-stroke motorcycles, self-mixing and for separated lubrication.
- can be used up to a mixing ratio of 1:100 (depending on manufacturer's recommendation)

CHARACTERISTICS / APPLICATION BENEFITS

- prevents carbonisation
- high protection from pollution
- nearly smokeless

APPROVALS

SPECIFICATIONS

RECOMMENDATIONS

API TC
JASO FD
ISO-L-EGD

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.835 – 0.875
Kin. Viscosity @ 40 °C	ASTM D7279	mm ² /s	35 – 65
Flash Point COC	DIN ISO 2592	°C	min. 130
Flash Point PM	DIN EN ISO 2719	°C	min. 100
Pour Point	ASTM D7346	°C	max. -30

Customs tariff number: 34031980

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 8)