

## AVISTA pure CF-4 SAE 10W-30

Universal engine oil for the mixed fleet (petrol older than 2001, diesel) where the requirements of API specification CF-4 and SJ are required. Offers a wide range of outstanding features.

### APPLICATION

- Commercial vehicles, cars (2001 and older), petrol, diesel

### CHARACTERISTICS

- aging resistance
- stability of viscosity
- fuel-saving
- low exhaust gas emissions
- engine cleanliness
- longer maintenance interval

### RECOMMENDATIONS

API CF-4  
API SJ

Klicken oder tippen Sie hier, um Text einzugeben.  
Klicken oder tippen Sie hier, um Text einzugeben.

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		10W-30
Density 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.845 – 0.875
Kin. Viscosity @ 100 °C	DIN 51562-1	mm <sup>2</sup> /s	10.8 – 12.2
Viscosity Index	DIN ISO 2909		min. 140
Total Base Number	DIN ISO 3771	mg KOH/g	7.3 – 9.3
Dyn. Viscosity @ -25°C	DIN 51377	mPa*s	max. 7,000
Flash point COC	DIN ISO 2592	°C	min. 220
Pour Point	DIN ISO 3016	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 3)