

AVISTA pure CF-4 SAE 15W-40

Universal engine oil for the mixed fleet (petrol older than 2001, diesel) where the requirements of API specification CF-4 and SJ are required. Offers a wide range of outstanding features.

APPLICATION

- Commercial vehicles, cars (2001 and older), petrol, diesel

CHARACTERISTICS

- aging resistance
- stability of viscosity
- fuel-saving
- low exhaust gas emissions
- engine cleanliness
- longer maintenance interval

RECOMMENDATIONS

API	CF-4
API	SJ

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		15W-40
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.845 – 0.885
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	14.3 – 15.7
Viscosity Index	ASTM D2270		min. 135
Total Base Number	ASTM D2896	mg KOH/g	7.0 – 8.8
Dyn. Viscosity @ -20°C	ASTM D5293	mPa*s	max. 7,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Nnummer 5)