

## AVISTA pure CF-4 SAE 20W-50

**Universal engine oil for the mixed fleet (petrol older than 2001, diesel) where the requirements of API specification CF-4 and SJ are required. Offers a wide range of outstanding features.**

### APPLICATION

- Commercial vehicles, cars (2001 and older), petrol, diesel

### CHARACTERISTICS

- Aging resistance
- stability of viscosity
- fuel-saving
- low exhaust gas emissions
- engine cleanliness
- longer maintenance interval

### RECOMMENDATIONS

API	CF-4
API	SJ

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		20W-50
Density 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.860 – 0.890
Kin. Viscosity @ 100 °C	DIN 51562-1	mm <sup>2</sup> /s	17.6 – 19.0
Viscosity Index	DIN ISO 2909		min. 135
Total Base Number	DIN ISO 3771	mg KOH/g	7.3 – 9.3
Dyn. Viscosity @ -15°C	DIN 51377	mPa*s	max. 9,500
Flash point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -24

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Nnummer 3)