

AVISTA pure EVO GER SAE 10W-40

High-quality engine oil for commercial vehicles (diesel Euro I-VI) of the AVISTA pure EVO line for meeting of all requirements of many OEM approvals/specifications, especially for German types of vehicle.

APPLICATION

- commercial vehicles, diesel (Euro I-VI), with modern after-treatment of exhaust gas

CHARACTERISTICS

- excellent piston cleanliness
- prevention of bore-polishing
- low wear and formation of soot
- stability of lubricant
- longer maintenance interval

APPROVALS

Deutz	DQC IV-18 LA
Mack	EO-N
MTU	TYPE 3.1
Renault	RLD-2
Volvo	VDS-3

SPECIFICATIONS

ACEA	E6/E7
MB	228.51
MAN	M3477, M3271-1

RECOMMENDATIONS

API	CJ-4
-----	------

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		10W-40
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.835 – 0.875
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	13.3 – 14.7
Viscosity Index	ASTM D2270		min. 150
Total Base Number	ASTM D2896	mg KOH/g	9.0 – 11.0
Dyn. Viscosity @ -25°C	ASTM D5293	mPa*s	max. 7,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 5)