

AVISTA pure EVO SWE SAE 10W-40

High-quality engine oil for commercial vehicles (diesel Euro I-V) of the AVISTA pure EVO line for meeting of all requirements of the ACEA specification E4/E7 and many OEM approvals/specifications. Suitable especially for Swedish types of vehicle.

APPLICATION

- Commercial vehicles, diesel (Euro I-V)

CHARACTERISTICS

- Excellent piston cleanliness
- prevention of bore-polishing
- low wear and formation of soot
- stability of lubricant
- longer maintenance interval

APPROVALS

Deutz	DQC III-18
Mack	EO-N
MAN	M3277
DTFR	15B120 (MB 228.5)
MTU	TYPE 3
Renault	RLD-2
Scania	LDF-3
Volvo	VDS-3

SPECIFICATIONS

ACEA	E4 E7
Cummins	CES 20072
DAF	Extended Drain
DTFR	15B110 (MB 228.3)

RECOMMENDATIONS

API	CF-4
-----	------

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		10W-40
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.845 – 0.885
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	12.5 – 13.9
Viscosity Index	ASTM D2270		min. 147
Total Base Number	ASTM D2896	mg KOH/g	14.6 – 17.0
Dyn. Viscosity @ -25 °C	ASTM D5293	mPa*s	max. 7,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 4)