

AVISTA pure EVO PRIME SWE SAE 10W-30

High quality and fuel saving high-performance engine oil for commercial vehicles (diesel Euro I-VI) of the AVISTA pure EVO PRIME line with extremely long maintenance interval and low ash. Developed especially for Swedish (and other) types of vehicle.

APPLICATION

- Commercial vehicles, diesel (Euro I-VI), with modern after-treatment of exhaust gas

CHARACTERISTICS / APPLICATION BENEFITS

- Fuel saving
- longer maintenance interval
- excellent piston cleanliness
- low wear and formation of soot
- lubricant stability
- resistance to aging
- stability of viscosity
- low exhaust gas emissions
- engine cleanliness
- little ash

APPROVALS

MAN	M3575
Scania	LA

SPECIFICATIONS

ACEA	E9
API	CJ-4
Cummins	CES 20081
Caterpillar	ECF-3
Daimler	MB 228.31
Detroit Diesel	DCC 93K218
Deutz	DQC III-18LA
Mack	EO-O PP
MTU	TYPE 2.1
Renault	RLD-3
Volvo	VDS-4

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		10W-30
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.845 – 0.875
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	11.0 – 12.0
Viscosity Index	DIN ISO 2909		min. 155
Total Base Number	DIN ISO 3771	mg KOH/g	7.8 – 9.9
Dyn. Viscosity @ -25°C	DIN 51377	mPa*s	max. 7,000
Flash point COC	DIN ISO 2592	°C	min. 210
Pour Point	DIN ISO 3016	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 3)