

## AVISTA pure EVO PRIME SWE SAE 10W-40

High quality and fuel saving high-performance engine oil for commercial vehicles (diesel Euro I-VI) of the AVISTA pure EVO PRIME line with extremely long maintenance interval and low ash. Developed especially for Swedish (and other) types of vehicle.

### APPLICATION

- commercial vehicles, diesel (Euro I-VI), with modern after-treatment of exhaust gas

### CHARACTERISTICS

- fuel saving
- longer maintenance interval
- excellent piston cleanliness
- low wear and formation of soot
- lubricant stability
- resistance to aging
- stability of viscosity
- low exhaust gas emissions
- engine cleanliness
- little ash

### APPROVALS

MB-Freigabe 228.51

### SPECIFICATIONS

ACEA	E6/E7/E9
API	CK-4
Cummins	CES 20081
Caterpillar	ECF-3
Detroit Diesel	DDC 93K218
Deutz	DQC IV-10LA
JASO	DH-2
Mack	EO-O PP
MAN	M3477, M3271-1
MTU	TYPE 3.1
Renault	RLD-3
Scania	LA
Volvo	VDS-4

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		10W-40
Density 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.835 – 0.875
Kin. Viscosity @ 100 °C	ASTM D7279	mm <sup>2</sup> /s	13.6 – 15.0
Viscosity Index	ASTM D2270		min. 152
Total Base Number	ASTM D2896	mg KOH/g	9.4 – 11.4
Dyn. Viscosity @ -25 °C	ASTM D5293	mPa*s	max. 7,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 7)