

AVISTA pace EVO C4 SAE 5W-30

Fuel-saving car engine oil (petrol, diesel) of the AVISTA pace EVO line for vehicles with modern after-treatment of exhaust gas and longer maintenance intervals for meeting of all requirements of the ACEA specification C5 and the OEM approvals stated.

APPLICATION

- car, light commercial vehicles, petrol, diesel, with modern after-treatment of exhaust gas
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

CHARACTERISTICS / APPLICATION BENEFITS

- low SAPS
- aging resistance
- stability of viscosity
- fuel-saving
- low exhaust gas emissions
- low wear
- engine cleanliness
- longer maintenance interval

APPROVALS

API	SN
Renault	RN 0720
MB-Approval	226.51

SPECIFICATIONS

ACEA	C4
------	----

RECOMMENDATIONS

MB	229.31
----	--------

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 5W-30
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.840 – 0.860
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	11.2 – 12.7
Viscosity Index	DIN ISO 2909		min. 165
Total Base Number	DIN ISO 3771	mg KOH/g	7.2 – 9.2
Dyn. Viscosity @ -30 °C	DIN 51377	mPa*s	max. 6.600
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 4)