

AVISTA pace SN SAE 5W-20

Universal passenger car engine oil for a wide range of vehicles, to meet all requirements of API specification SN.

APPLICATION

- Car, petrol

CHARACTERISTICS

- Small deposits and wear
- better properties than API SM referring resistance to aging
- stability of viscosity
- fuel saving
- low exhaust gas emission
- engine cleanliness, piston cleanliness
- flexible maintenance intervals

APPROVALS

API SN

SPECIFICATIONS

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 5W-20
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.840 – 0.860
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	7.4 – 8.9
Viscosity Index	DIN ISO 2909		min. 155
Total Base Number	DIN ISO 3771	mg KOH/g	7.5 – 9.0
Dyn. Viscosity @ -30°C	DIN 51377	mPa*s	max. 6.600
Flash point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	-36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 3)