

AVISTA pace EVO FE SAE 5W-30

Highly-modern and extremely fuel-saving car engine oil (petrol, diesel) of the AVISTA pace EVO line for vehicles with modern after-treatment of exhaust gas and long-life service intervals for meeting of all requirements the OEM approvals/specifications stated. Especially developed to prevent low-speed pre-ignition (LSPI). Not suitable for R5 and V10 pump-injector engines (according to VW 506 01).

APPLICATION

- Car, light commercial vehicles, petrol, diesel, with modern after-treatment of exhaust gas

CHARACTERISTICS

- low-speed pre-ignition (LSPI) prevention
- reduced SAPS
- extremely fuel-saving
- low evaporation loss
- aging resistance
- stability of viscosity
- low exhaust gas emissions
- low wear
- engine cleanliness
- longer maintenance interval

APPROVALS

API	SP
BMW	LL 04
MB-Freigabe	229.52 229.51 229.31
VW	504 00 / 507 00
Porsche	C30

SPECIFICATIONS

ACEA	C3
API	SN Plus

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 5W-30
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	10.9 – 12.3
Viscosity Index	ASTM D2270		min. 165
Total Base Number	ASTM D2896	mg KOH/g	7.7 – 9.7
Dyn. Viscosity @ -30°C	ASTM D5293	mPa*s	max. 6.600
Flash Point COC	DIN ISO 2592	°C	min. 220
Pour Point	ASTM D7346	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 7)