

AVISTA pace ASIA SAE 10W-50

Universal passenger car engine oil for a wide range of vehicles, to meet all requirements of API specification SP.

APPLICATION

- car, petrol
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)
- Suitable for models of BYD, Chevrolet, Hyundai, Infinity, Kia, Lexus, Mazda, Mitsubishi, Nissan, Tata, Toyota and others

CHARACTERISTICS

- small deposits and wear
- better properties than API SM referring resistance to aging
- stability of viscosity
- fuel saving
- low exhaust gas emission
- engine cleanliness
- piston cleanliness
- flexible maintenance intervals

RECOMMENDATIONS

API SP

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 10W-50
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	16.5 – 18.3
Viscosity Index	ASTM D2270		min. 160
Total Base Number	ASTM D2896	mg KOH/g	6.2 – 8.2
Dyn. Viscosity @ -25 °C	ASTM D5293	mPa*s	max. 7.000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 2)