

AVISTA pace ASIA SAE 10W-30

Universal passenger car engine oil for a wide range of vehicles, to meet all requirements of API specification SP. Specially developed to fulfill the requirements of Asian OEM, but also many more.

APPLICATION

- car, petrol
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)
- Suitable for models of Chery, Chevrolet, Honda, Hyundai, Kia, Lexus, Mazda, Mitsubishi, Nissan, Suzuki, Tata, Toyota, and others

CHARACTERISTICS

- small deposits and wear
- better properties than API SM referring resistance to aging
- stability of viscosity
- fuel saving
- low exhaust gas emission
- engine cleanliness
- piston cleanliness
- flexible maintenance intervals

SPECIFICATIONS

API	SP Resource Conserving
ILSAC	GF-6

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 10W-30
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	9.4 – 11.2
Viscosity Index	DIN ISO 2909		min. 133
Total Base Number	DIN ISO 3771	mg KOH/g	6.2 – 8.2
Dyn. Viscosity @ - 25°C	DIN 51377	mPa*s	max. 7.000
Flash Point COC	DIN ISO 2592	°C	min. 220
Pour Point	DIN ISO 3016	°C	max. -30

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 2)