

## AVISTA pace ASIA SAE 5W-50

Universal passenger car engine oil for a wide range of vehicles, to meet all requirements of API specification SP. Specially developed to fulfill the requirements of Asian OEM, but also many more

### APPLICATION

- car, petrol
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)
- Suitable for models of Lexus, Mitsubishi, SsangYong, and others

### CHARACTERISTICS

- small deposits and wear
- better properties than API SM referring resistance to aging
- stability of viscosity
- fuel saving
- low exhaust gas emission
- engine cleanliness
- piston cleanliness
- flexible maintenance intervals

### RECOMMENDATIONS

API                      SP

### TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		SAE 5W-50
Density 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm <sup>2</sup> /s	17.0 – 18.8
Viscosity Index	ASTM D2270		min. 175
Total Base Number	ASTM D2896	mg KOH/g	6.4 – 8.4
Dyn. Viscosity @ -30 °C	ASTM D5293	mPa*s	max. 6,600
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -33

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 2)