

AVISTA pace ASIA SAE 5W-30

Universal passenger car engine oil for a wide range of vehicles, to meet all requirements of API specification SP (RC). Specially developed to fulfill the requirements of Asian OEM, but also many more.

APPLICATION

- car, petrol
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)
- Suitable for models of Chery, Chevrolet, Honda, Hyundai, Kia, Lexus, Mazda, Mitsubishi, Nissan, Suzuki, Tata, Toyota, and others

CHARACTERISTICS

- small deposits and wear
- better properties than API SM referring resistance to aging
- stability of viscosity
- fuel saving
- low exhaust gas emission
- engine cleanliness
- piston cleanliness
- flexible maintenance intervals

APPROVALS

API SP
Resource Conserving

SPECIFICATIONS

ILSAC GF-6

TYPICAL CHARACTERISTICS

(The given data are typical data.)

| Parameter | Method | Unit | |
|-------------------------|------------------|--------------------|---------------|
| SAE Class | SAE J 300 | | SAE 5W-30 |
| Density @ 15 °C | DIN EN ISO 12185 | g/cm ³ | 0.830 – 0.870 |
| Kin. Viscosity @ 100 °C | ASTM D7279 | mm ² /s | 9.6 – 11.4 |
| Viscosity Index | ASTM D2270 | | min. 150 |
| Total Base Number | ASTM D2896 | mg KOH/g | 6.3 – 8.3 |
| Dyn. Viscosity @ -30 °C | ASTM D5293 | mPa*s | max. 6.600 |
| Flash Point COC | DIN ISO 2592 | °C | min. 200 |
| Pour Point | ASTM D7346 | °C | max. -36 |

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 2)